

3HP BX25



ALUMINUM CYLINDER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX29/50CM3	BX25	50	3	220	295	10	1620	85 X 38 X 73	43
BX29/100CM3	BX25	100	3	220	295	10	1620	108 X 40 X 80	58
BX29/150CM3	BX25	150	3	220	295	10	1620	132 X 45 X 92	73
BX29/200CM3	BX25	200	3	220	295	10	1620	145 X 46 X 92	88
BX29/270CM3	BX25	270	3	220	295	10	1620	155 X 57 X 112	106
BX29/50CT3	BX25	50	3	380	295	10	1620	85 X 38 X 73	43
BX29/100CT3	BX25	100	3	380	295	10	1620	108 X 40 X 80	58
BX29/150CT3	BX25	150	3	380	295	10	1620	132 X 45 X 92	73
BX29/200CT3	BX25	200	3	380	295	10	1620	145 X 46 X 94	88

CAST IRON CYLINDER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX29G/50CM3	BX25G	50	3	220	295	10	1620	85 X 38 X 73	45
BX29G/100CM3	BX25G	100	3	220	295	10	1620	108 X 40 X 80	60
BX29G/150CM3	BX25G	150	3	220	295	10	1620	132 X 45 X 92	75
BX29G/200CM3	BX25G	200	3	220	295	10	1620	145 X 46 X 92	90
BX29G/270CM3	BX25G	270	3	220	295	10	1620	155 X 57 X 112	108
BX29G/50CT3	BX25G	50	3	380	295	10	1620	85 X 38 X 73	45
BX29G/100CT3	BX25G	100	3	380	295	10	1620	108 X 40 X 80	60
BX29G/150CT3	BX25G	150	3	380	295	10	1620	132 X 45 X 92	75
BX29G/200CT3	BX25G	200	3	380	295	10	1620	145 X 46 X 94	90