



ALUMINUM CYLINDER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX49/270CM3	BX49	270	3	220	423	10	1100	155 X 57 X 112	116
BX49/100CT4	BX49	100	4	380	541	10	1400	108 X 41 X 85	68
BX49/150CT4	BX49	150	4	380	541	10	1400	132 X 50 X 103	83
BX49/200CT4	BX49	200	4	380	541	10	1400	145 X 50 X 170	98
BX49/270CT4	BX49	270	4	380	541	10	1400	155 x 57 X 112	116

CAST IRON CYLINDER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX49G/270CM3	BX49G	270	3	220	423	10	1100	155 X 57 X 112	120
BX49G/100CT4	BX49G	100	4	380	541	10	1400	108 X 41 X 85	72
BX49G/150CT4	BX49G	150	4	380	541	10	1400	132 X 50 X 103	87
BX49G/200CT4	BX49G	200	4	380	541	10	1400	145 X 50 X 170	102
BX49G/270CT4	BX49G	270	4	380	541	10	1400	155 x 57 X 112	120