



- COAXIAL DRIVE screw compressor on tank with metal cabinet and dryer*
- Oil separator filter SPIN-ON*
- Oil filter SPIN-ON*
- Oil/air cooling through electrically aired radiator*
- Operating load and load with timed shutdown*
- Delta-star starting*
- Electronic control card*
- Dryer with BY-PASS equipped*
- On demand is available version with "inverter"*

TECHNICAL SPECIFICATIONS

| MODEL | HP | BAR | AIR Delivered (Lt/min) | Volt/ph/Hz | db-A | TANK | SIZE | KG |
|------------------|-----|-----|------------------------|------------|------|------|----------------|-----|
| DMBV-270-7,5-8E | 7,5 | 8 | 820 | 400/3/50 | 66 | 270 | 160 X 55 X 145 | 268 |
| DMBV-270-7,5-10E | 7,5 | 10 | 780 | 400/3/50 | 66 | 270 | 160 X 55 X 145 | 268 |
| DMBV-270-10-8E | 10 | 8 | 1050 | 400/3/50 | 66 | 270 | 160 X 55 X 145 | 270 |
| DMBV-270-10-10E | 10 | 10 | 1000 | 400/3/50 | 66 | 270 | 160 X 55 X 145 | 270 |
| DMBV-270-15-8E | 15 | 8 | 1650 | 400/3/50 | 66 | 270 | 160 X 55 X 145 | 300 |
| DMBV-270-15-10E | 15 | 10 | 1500 | 400/3/50 | 66 | 270 | 160 X 55 X 145 | 300 |
| DMBV-270-20-8E | 20 | 8 | 2000 | 400/3/50 | 67 | 270 | 160 X 55 X 145 | 320 |
| DMBV-270-20-10E | 20 | 10 | 1850 | 400/3/50 | 67 | 270 | 160 X 55 X 145 | 320 |
| DMBV-500-7,5-8E | 7,5 | 8 | 820 | 400/3/50 | 66 | 500 | 195 X 68 X 164 | 330 |
| DMBV-500-7,5-10E | 7,5 | 10 | 780 | 400/3/50 | 66 | 500 | 195 X 68 X 164 | 330 |
| DMBV-500-10-8E | 10 | 8 | 1050 | 400/3/50 | 66 | 500 | 195 X 68 X 164 | 332 |
| DMBV-500-10-10E | 10 | 10 | 1000 | 400/3/50 | 66 | 500 | 195 X 68 X 164 | 332 |
| DMBV-500-15-8E | 15 | 8 | 1650 | 400/3/50 | 66 | 500 | 195 X 68 X 164 | 380 |
| DMBV-500-15-10E | 15 | 10 | 1500 | 400/3/50 | 66 | 500 | 195 X 68 X 164 | 380 |
| DMBV-500-20-8E | 20 | 8 | 2000 | 400/3/50 | 67 | 500 | 195 X 68 X 164 | 405 |
| DMBV-500-20-10E | 20 | 10 | 1850 | 400/3/50 | 67 | 500 | 195 X 68 X 164 | 405 |