

12.1 AIR DRYERS

Max ambient temperature: 45°C
Max inlet air temperature: 55°C
Max inlet air pressure: 16 bar
Standard Dew Point: 5°Cat 7 bar

On demand the refrigerated air dryers can be produced for high temperature (ambient 50°C -inlet 100°C) and high pressure up to 50 bar



TECHNICAL SPECIFICATIONS

MODEL	Compressor Combination	N Lt/min	N m ³ /h	Connections	Dimensions mm.	Weight Kg.
AD3	4HP	350	21	3/8	310 X 345 X 435	21
AD6	5,5HP	600	36	1/2	370 X 515 X 475	25
AD9	7,5HP	950	57	1/2	370 X 515 X 475	26
AD12	10HP	1200	72	1/2	370 X 515 X 475	28
AD18	15HP	1800	108	1/2	370 X 515 X 475	32
AD25	20HP	2500	150	1"	345 X 420 X 740	34
AD32	25HP	3200	192	1". 1/4	345 X 445 X 740	39
AD43	30HP	4300	258	1". 1/4	345 X 445 X 740	40
AD52	30HP	5200	312	1". 1/4	345 X 445 X 740	41
AD61	40HP	6100	366	1". 1/2	555 X 580 X 885	54
AD75	50HP	7500	450	1". 1/2	555 X 580 X 885	56
AD105	75HP	10500	630	2"	555 X 625 X 975	94
AD130	75HP	13000	780	2"	555 X 625 X 975	96
AD168	120HP	16800	1008	2". 1/2	665 X 725 X 1105	144